

Manufacturer **Adolf Würth GmbH & Co. KG**
Product Name **Assembly Adhesive (0893 100 100)**
Product Rating

- The product fulfills the requirements of action level 1 to 4 and contributes to achieve 10 (of max. 10) criterion points within Criterion 06 'Risks for the regional environment'.

Criterion 06 Risks for the Local Environment - Ecological Quality
Action Level 1 1 Point

Action Level 2 5 Points

Action Level 3 7.5 Points

Action Level 4 10 Points

Criterion 08 Sustainable Resources - Ecological Quality*
Action Level 1 5 Points

Action Level 2 7.5 Points

Action Level 3 10 Points


* This criterion is only applicable to wooden materials.

Product Characteristics

Solvent- free adhesive based on acrylic dispersion with high initial strength for adhering various materials indoors. May be painted and coated

About DGNB Products - www.dgnb.de

This declaration helps to assess products easily according the certification system DGNB® Neubauversion Büro- und Verwaltungsgebäude (NBV09). Products are not reviewed or certified by DGNB. DGNB credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. Therefore the project team or the manufacturer is responsible to declare the compliance with the project requirements to achieve DGNB points.

Below you find an explanation of the symbols. Detailed information are on the next pages.



Credit requirements fulfilled - the action level is achieved



Credit is not applicable to this product

22%

X% of the product comply with the credit requirement



Required data not specified - for required data contact manufacturer



Credit requirements are not fulfilled

Manufacturer **Adolf Würth GmbH & Co. KG**

Product Name **Assembly Adhesive (0893 100 100)**

Criterion 06 Risks for the Local Environment - Ecological Quality

Detailed Rating

No	Product Name	Manufacturer
A1	Assembly Adhesive (0893 100 100)	Adolf Würth GmbH & Co. KG
Product Type	Requirement	Contribution of Product
Sealants, adhesives, and anti-corrosion Applied on mineral and non-mineral surfaces.	Action Level 4: VOC-content < 3% Action Level 3: VOC-content < 10% Action Level 2: VOC-content < 15%; RAL UZ 12a count as proof Action Level 1: VOC-content < 25%	VOC-content: <1.5%